

PLINIUS
THE HEART OF MUSIC

M 8
PRE AMPLIFIER



M 8 P R E A M P L I F I E R

The PLINIUS Odeon development has created the direction for a new range of Preamplifiers and Amplifiers. The M8 is a new and exciting Preamplifier utilising a new chassis and circuit topology resulting in a very competitively priced control unit capable of state of the art performance.

The power supply has been developed to provide an extremely low impedance, allowing the audio circuitry to deliver its best.

The only visible control on the M8 is the rotary volume knob with all other functions driven from the distinctive remote and indicated on the front panel display.

Several aspects of previous PLINIUS Preamplifiers have been continued in the M8 including low noise, low distortion J FET input circuitry and the very best of discrete componentry.

The M8 will allow the connection of up to 5 source components including both balanced and single ended connection for CD, A Processor Loop allows full integration with a home theatre system. Balanced output facilities are available for those requiring this standard of connection to a power amplifier.

The chassis has been fashioned from robust materials which include a forged and anodised fascia of gratifying solidity.

Specifications For PLINIUS M8

Frequency Response:

20Hz to 20kHz +/-0.2dB

Distortion:

Typically <0.05% THD at rated output level

Hum & Noise:

-98dBV, A weighted

Gain:

All inputs: 12dB

Input Impedance:

50k Ohms

Rated Output Level:

500mV RMS into 10k Ohms or higher

Output Source Impedance:

Typically 100 Ohms

Dimensions:

Height: 90mm (3 1/2")

Width: 450mm (17 3/4")

Depth: 380mm (15")

Weight: 5.5kg (12lbs)



PLINIUS

Plinius Audio Limited
PO Box 1836, Palmerston North
New Zealand

Ph +64 6 354 8583

Fax +64 6 354 8586

Email info@pliniusaudio.com

www.pliniusaudio.com